



Chemical Methods, Inc.

20338 Progress Drive
Cleveland, Ohio 44149
216/476-8400
FAX: 216-476-1231
www.chemicalmethods.com

TECHNICAL DATA SHEET

CM-5003-LT MULTI-METAL SPRAY CLEANER

PRODUCT DESCRIPTION

CM-5003-LT is a mildly alkaline cleaner designed for spray cleaning of zinc, aluminum, and most other alloys including castings, sheet stock, extrusions, and tubing. **CM-5003-LT** is effective in hard water and does not leave sludge or scale build-up that occurs with the use of heavily silicated cleaners.

- Low Residue
- Non-Silicated
- Concentrated Formula
- Low Foaming

PHYSICAL AND CHEMICAL PROPERTIES

Appearance, Concentrate	Clear Brown Liquid
Specific Gravity	1.145
Pounds per Gallon	9.56
pH	9.9 +/- 0.2

Parameter	Range
Concentration	2% to 10%
Temperature	120°F to 180°F
Time	30 to 120 seconds
Pressure	15 to 60 psi

Note: Operating at higher concentrations will allow lower temperatures and shorter timeframes. Exact concentration, temperature and time will vary depending on soil types and amounts, system capabilities, part configuration, and part racking. Additions of CM-DF#31 may be necessary to control foam at lowest temperatures.

SAFETY AND HANDLING

Refer to material safety data sheet for additional information about this product.